

## LY-SERIES LED WATERPROOF PANEL LIGHTS

### FEATURES

- > Warranty 5 years
- > Waterproof IP54-IP65
- > Power Saving > 50%
- > Life Cycle 50,000 hrs.
- > Instant On No warm up time
- > Non-Flicker No flicker effect that causes fatigue
- > High Uniformity Uniform light distribution
- > No UV No-UV or IR light emitted, does not attract insects
- > Low Heat Lower heat than fluorescent leading to savings in A/C costs
- > No mercury Contains no toxic mercury
- > Architectural Design 11mm Slimline attractive design
- Maintenance Free
- > Application Commercial Buildings, Schools, Hospitals, Retail Shops, Laboratories, Galleries



Photometric Files Available on Request

### SPECIFICATIONS

- > Input Voltage AC 85-265V 50/60Hz
- > Beam Angle 120 deg
- > Operating Temp neg 10 to 40 deg C
- > Storage Temp neg 20 to 60 deg C
- > Operating Humidity 10-80%
- > IK Rating IK04
- > IP Rating IP41
- > Fixing Methods Recessed  
Surface Mount (Optional)  
Suspended (Optional)
- > Colour Temp 2700-3300K (Warm White)  
4000-5000K (Pure White)  
5500-7000K (Cool White)
- > CRI >80

### VERSIONS

Model	Size (mm)	Power (W)	Flux (lm)
> LY-66B-IP65	600*600	50W	4250
> LY-66C-IP65	600*600	40W	3400
> LY-66F-IP65	600*600	60W	5400