


Lo5G-DM DALI DIMMABLE LED TUBE

T8 Fluorescent Tube Replacement

FEATURES		PHOTO		
> Warranty	3 years	 <p>FCCE RoHS</p>		
> Power Saving	50% +			
> Life Cycle	50,000 hrs			
> Low Maintenance	Robust construction			
> Instant On	No warm up time			
> Non-Flicker				
> No-UV	No-UV or IR light emitted			
> Low heat	Less heat than fluorescent tubes, leading to savings in A/C costs.			
> No Mercury	Contains no toxic mercury			
> No glass	Aluminium and High Strength Polycarbonate construction			
> Adjustable	Tombstones adjustable so that beam angle can be positioned as required.			
> Power Supply	Isolated power supply			
> Dimmable	For use with Dali system			
> Application	Office, Shopping Centre, Car Park, Airport, Commercial Buildings...			
SPECIFICATIONS		VERSIONS		
> Voltage Range	AC 100-240V	> 600mm	Power	11W
> Frequency	50/60Hz		Size	26 x 588mm
> Beam Angle	120 deg		LEDs	108 pcs
> Power Factor	> 0.95		Lumens (Frosted)	1045
> Power Efficiency	> 0.90		Lumens (Clear)	1155
> Operating Temp	neg 20 to 40 degC	> 900mm	Power	20W
> Light Source	SMD 3528 LED		Size	26 x 894mm
> Lens	Clear/Frosted		LEDs	216pcs
> CRI	> 80		Lumens (Frosted)	1900
> Housing	Aluminium and High Strength Polycarbonate		Lumens (Clear)	2100
> Life Cycle	50,000 hrs	> 1200mm	Power	20W
> Lumen/Watt	105/95		Size	26 x 1198mm
	Warm White(3000K)		LEDs	216pcs
	Daylight White(4000K)		Lumens (Frosted)	1900
> Colour Range	Pure White(5500K)	> 1500mm	Lumens (Clear)	2100
	Cool White (6500K)		Power	24W
			Size	26 x 1498mm
			LEDs	240pcs
			Lumens (Frosted)	2280
			Lumens (Clear)	2520

Lightsense Australia Pty Ltd

TEL 1300 944 822 EML info@lightsense.com.au

WEB www.lightsense.com.au ADD PO Box 613, West Perth WA 6872