

Lo6G-V "V" SHAPE LED TUBE

T8 Fluorescent Tube Replacement

FEATURES		PHOTO	
> Warranty	3 years		
> Power Saving	50% +		
> Life Cycle	50,000 hrs		
> Low Maintenance	Robust construction		
> Instant On	No warm up time		
> Non-Flicker			
> No-UV	No-UV or IR light emitted		
> Low heat	Less heat than fluorescent tubes, leading to savings in A/C costs.		
> No Mercury	Contains no toxic mercury		
> No glass	Aluminium and High Strength Polycarbonate construction		
> Adjustable	Tombstones adjustable		
> Application	Refrigerator, Freezer, ATM, Light-Box, Subway		
> V-Shaped Beam			
SPECIFICATIONS			
> Voltage Range	AC 100-240V	> 600mm	Power 15W
> Frequency	50/60Hz		Size 26 x 588mm
> Beam Angle	220 deg		LEDs 144pcs
> Power Factor	> 0.95		Lumens (Frosted) 1425
> Power Efficiency	> 0.90		Lumens (Clear) 1575
> Operating Temp	neg 20 to 40 degC	> 900mm	Power 17W
> Light Source	SMD 3528 LED		Size 26 x 894mm
> Lens	Clear/Frosted		LEDs 168 pcs
> CRI	> 80		Lumens (Frosted) 1615
> Housing	Aluminium and High Strength Polycarbonate		Lumens (Clear) 1785
> Life Cycle	50,000 hrs	> 1200mm	Power 20W
> Lumen/Watt	105/95		Size 26 x 1198mm
> Colour Range	Warm White(3000K) Daylight White(4000K) Pure White(5500K) Cool White (6500K)		LEDs 220 pcs
		> 1500mm	Lumens (Frosted) 1900
			Lumens (Clear) 2100
			Power 24W
			Size 26 x 1498mm
			LEDs 240pcs
			Lumens (Frosted) 2280
			Lumens (Clear) 2520