


LY-33-R2/LY-36-R2 300 x 300/300 x 600 LED PANEL

Fluorescent Tube Replacement

FEATURES		PHOTO	
<ul style="list-style-type: none"> > Warranty 3 years > Power Saving 50% + > Life Cycle 50,000 hrs. > Instant On No warm up time > Non-Flicker > High Uniformity Uniform light distribution > No UV No-UV or IR light emitted, does not attract insects > Low Heat Less Heat than fluorescent tubes leading to savings in A/C costs > No mercury Contains no toxic Mercury > Architectural Design Slimline attractive design > Maintenance Free > Remote Control Optional remote control > Dimmable Optional dim function > Application Commercial Buildings, Schools, Hospitals, Retail Shops, Laboratories, Galleries 			
SPECIFICATIONS		VERSIONS	
<ul style="list-style-type: none"> > Voltage Range AC 100-240V > Beam Angle 160 deg > Operating Temp neg 10 to 40 deg C > Storage Temp neg 20 to 40 deg C > Operating Humidity 10-80% > IK Rating IK04 > IP Rating IP41 > Fixing Methods Recessed Surface Mount (Optional) Suspended (Optional) > Colour Temp 2700-3300K (Warm White) 4000-5000K (Pure White) 5500-7000K (Cool White) 		<ul style="list-style-type: none"> > LY-33-R2 <ul style="list-style-type: none"> Power 18W Size 298 X 298 X 13mm Weight 2.5 kgs Lumens 950lm (Cool White) 915lm (Pure White) 750lm (Warm White) > LY-36C-R2 <ul style="list-style-type: none"> Power 28W Size 298 X 598 X 13mm Weight 2.6 kgs Lumens 2300lm (Cool White) 2100lm (Pure White) 1900lm (Warm White) > 	

Lightsense Australia Pty Ltd

TEL 1300 944 822 EML info@lightsense.com.au

WEB www.lightsense.com.au ADD PO Box 613, West Perth WA 6872