

LY-SR SQUARE-ROUND LED PANEL LIGHT

Fluorescent Down light Replacement

FEATURES PHOTO

Warranty 3 years
Power Saving > 50%
Life Cycle 50,000 hrs.
Instant On No warm up time

> Non-Flicker No flicker effect that causes fatigue

> **High Uniformity** Uniform light distribution

No-UV or IR light emitted, does not

attract insects

Low heat than fluorescent leading

to savings in A/C costs

Contains no toxic mercury, lead or

other hazardous materials

> Architectural Design Slimline attractive design

> Maintenance Free

> **Dimmable** Dimmable

Commercial Buildings, Schools,

> **Application** Hospitals, Retail Shops,

Laboratories, Galleries



SPECIFICATIONS

> Input Voltage 24V DC

Operating Temp neg 10 to 40 deg C
Storage Temp neg 20 to 60 deg C

Operating Humidity 10-80%
IK Rating IK04
IP Rating IP41

Recessed

> **Fixing Methods** Surface Mount (Optional)

Suspended (Optional)

2700-3300K (Warm White)

> Colour Temp 4000-5000K (Pure White)

5500-7000K (Cool White)

VERSIONS

LY-SR184-7W

Size

184 x 184 x 19mm

Power 7W

Lumens 380

380-450lm

LY-SR240-15W

Size

240 x 240 x 19mm

Power

15W

Lumens

700-1000lm