

MAXLITE & ULTIMATE LED FLOODLIGHTS 100W-960W 150W-2500W HID/MH Replacement



SPECIFICATIONS

> Voltage Range	AC 90-305V 50/60Hz
> Power Factor	> 0.98
> Operating Temp	neg 40 to 50 degC
> Light Source	Maxlite - Philips Lumileds 3030 Ultimate - Philips Luxeon 5050
> Driver	Meanwell Maxlite - Ultimate -
> Lens/Beam Pattern	30°,60°,90°,120°,60°/135°,85°/135° Ultimate - 30°,60°,120°,85°/135°
> Housing & Finish	Die-Cast Aluminium, Grade 316 Stainless, Marine Grade Powder Coat
> Body Colours	Black, White, Grey, RAL
> Lumen/Watt	Maxlite - 130Lm/w Ultimate - 140Lm/w
> IP Rating	IP65
> IK Rating	IK10
> Colour Temp	2700K-6500K
> CRI	> Ra80
> Control & Dimming Options	DMX512, DALI, 1-10V Zigbee Wi-Fi Wireless
> Warranty	6 Years
> Life Cycle	62,000 + hours
> Australian Compliance	AS/NZS 60598.2.5:2005

VERSIONS

		MAXLITE			
Code	Power	Lumens	Size (inc bracket)	Net Weight	
> ONOR-FL-100W	100W	13000Lm	321x377x91	4.5kg	
> ONOR-FL-150W	150W	19500Lm	418x376x91	6.5kg	
> ONOR-FL-200W	200W	26000Lm	526x376x91	9.0kg	
> ONOR-FL-250W	250W	32500Lm	631x376x91	11.5kg	
> ONOR-FL-300W	300W	39000Lm	444x506x148	12.5kg	
> ONOR-FL-400W	400W	52000Lm	654x506x148	19kg	
> ONOR-FL-500W	500W	65000Lm	654x506x148	20kg	
> ONOR-FL-600W	600W	78000Lm	763x506x148	23kg	
		ULTIMATE			
Code	Power	Lumens	Size (inc bracket)	Net Weight	
> ONOR-SFL-800W	800W	115,594	835x655x132	38.7kg	
> ONOR-SFL-960W	960W	137,518	990x655x132	45.3kg	