

RL2N JUPITER CARPARK / FOOTPATH / CYCLEWAY LUMINAIRE

FEATURES

- > Warranty 5 years
- > Power Saving 60% +
- > Life Cycle 50,000hrs
- > Low Maintenance Robust Construction. High-Shock and High-Vibration tolerance
- > Heat Dissipation Patented heat dissipation design achieves optimal efficiency
- > Modular Design LED Banks replaceable to allow for different lenses/application
- > Instant On No warm up time
- > High CRI Better representation of the colour spectrum
- > Low Heat Less heat produced than HID lights reduces risk of overheating/fire
- > Clean light Contains no mercury
- > Application Car Park, Footpath, Cycleway, Private Road



Photometric Files Available at www.lightsense.com.au

SPECIFICATIONS

- > Voltage Range AC 120-277V
- > Frequency 50/60Hz
- > Working Current 700MA
- > Power Factor > 0.92
- > Power Efficiency > 0.85
- > Operating Temp neg 40 to 50 degC
- > Operating Humidity 10% to 95%
- > Light Source Cree LEDs
- > Driver Phillips
- > CRI >70
- > Housing Die-Cast Aluminium
- > Lumen/Watt >90
- > Spigot Mounting Max 50mm OD - adaptors available
- > IP Rating IP65
- > IK Rating IK08
- > Colour Temp 3000-5000K

VERSIONS

	Code	Power	LEDs	Lumens	Net Weight
>	RL2N2001	22W	10pcs	1,800	3kg
>	RL2N2002	45W	20pcs	3,600	3.1kg
>	RL2N2003	67W	30pcs	5,400	3.4kg