

RL2R1 APOLLO LED SOLAR STREET / CARPARK LUMINAIRE

FEATURES

- > Warranty 5 years
- > Life Cycle 50,000hrs - Luminaire
- > Low Maintenance Robust Construction. High-Shock and High-Vibration tolerance
- > Heat Dissipation Patented heat dissipation design achieves optimal efficiency
- > Modular Design LED Banks replaceable to allow for different lenses/application
- > Adjustable Knuckle Adjustable knuckle to allow for up-cast from 0 to 90 degrees
Lab tested to meet individual elements of AS1158-6 and Road-tested in the harshest Australian conditions
- > Tested
- > Instant On No warm up time
- > High CRI Better representation of the colour spectrum
- > Low Heat Less heat produced than HID lights reduces risk of overheating/fire
- > Clean light Contains no mercury
- > Application Road, Car Park



Photometric Files Available at www.lightsense.com.au

SPECIFICATIONS

- > Voltage Range DC 12-24V
- > Working Current 700MA
- > Power Efficiency > 0.9
- > Operating Temp neg 40 to 50 degC
- > Operating Humidity 10% to 95%
- > Light Source Cree LEDs
- > Driver Phillips
- > Lens/Beam Pattern Selectable. AS1158 compliant
- > CRI >70
- > Housing Die-Cast Aluminium
- > Lumen/Watt >100
- > Spigot Mounting Max 60mm OD
- > UWLR 0%
- > IP Rating IP65
- > IK Rating IK09
- > Colour Temp Warm, Day, Pure, Cool-White

VERSIONS

	Code	Power	LEDs	Lumens	Net Weight
>	RL2R1014	30W	14pcs	2,700	7.9kg
>	RL2R1028	60W	28pcs	5,400	8.8kg
>	RL2R1042	90W	42pcs	9,000	9.4kg