

## TL2R ARTEMIS LED TUNNEL LIGHT LUMINAIRE

150W - 400W HID Replacement

### FEATURES

- > Warranty 5 years
- > Power Saving 60% +
- > Life Cycle 50,000hrs
- > Low Maintenance Robust Construction. High-Shock and High-Vibration tolerance
- > Heat Dissipation Patented heat dissipation design achieves optimal efficiency
- > Modular Design LED Banks replaceable to allow for different lenses/application
- > Mounting Adjustable Wall Mount
- > Instant On No warm up time
- > High CRI Better representation of the colour spectrum
- > Low Heat Less heat produced than HID lights reduces risk of overheating/fire
- > Clean light Contains no mercury
- > Application Tunnel



Photometric Files Available at [www.lightsense.com.au](http://www.lightsense.com.au)

### SPECIFICATIONS

- > Voltage Range AC 100-277V
- > Frequency 50/60Hz
- > Working Current 700MA
- > Power Factor > 0.95
- > Power Efficiency > 0.92
- > Operating Temp neg 40 to 50 degC
- > Operating Humidity 10% to 95%
- > Light Source Cree LEDs
- > Driver Phillips
- > Lens/Beam Pattern Selectable
- > CRI >75
- > Housing Die-Cast Aluminium
- > Lumen/Watt 90
- > IP Rating IP65
- > Fixture Colour Options Black, Grey, White, Brown
- > Colour Temp Options Warm, Daylight, Pure, Cool-White

### VERSIONS

	Code	Power	LEDs	Lumens	Net Weight
>	TL2R2802	62W	28pcs	5,400	6.8kg
>	TL2R2803	93W	42pcs	8,100	7.6kg
>	TL2R2804	123W	56pcs	10,800	9.6kg
>	TL2R2805	155W	70pcs	13,500	10.5kg
>	TL2R2806	185W	84pcs	16,200	11.2kg
>	TL2R2807	216W	98pcs	18,900	12.3kg
>	TL2R2808	246W	112pcs	22,800	13.1kg
>	TL2R2809	277W	126pcs	25,650	13.4kg
>	TL2R2810	308W	140pcs	28,500	14.8kg